

Weatherproof high speed, PTZ day/night camera with IR lighting ideal for mobile surveillance



FEATURES

- Infrared LED range up to 260 ft. (80 m) for nighttime viewing
- Heavy duty die-cast aluminum casing
- Weatherproof standard IP66
- Shockproof; ideal for vehicle-mounted surveillance
- 360° continuous rotation, tilt angle up to 180°
- 6 patterns, each with 16 preset positions
- 128 preset positions
- Input voltage: 10.5 ~18 VDC

SPECIFICATIONS

Image Sensor:	1/4" SONY CCD
Effective Pixels (H x V)	
V1495M-26:	NTSC:768 x 494; PAL: 752 X 582
Sync. System:	Internal
Video Output:	VBS composite 1.0 V _{pp} , 75 Ohm
White Balance:	Auto/Manual
Resolution:	480 TV lines
Signal/Noise Ratio	
V1495M-26:	>50 dB
Electronic Shutter:	
V1495M-26:	1/3~ 1/10000 sec
Minimum Illumination:	0.0 lux
Focal Length	
V1495M-26:	f=3.5~91.0 mm
Iris & Zoom:	Automatic/Manual
Pan Preset Speed:	100°/s
Tilt Preset Speed:	60°/s
Pan Speed:	0° ~ 80°/s
Tilt Speed:	0° ~ 40°/s
Pan Range:	360° continuously
Tilt Range:	+90° ~ -90°
Preset Track:	128 presets, 6 tracks
Communication:	Multi-protocol, baud rate from 2400 ~ 19200 Bps for optional, RS-485 control
Power Supply:	10.5 VDC ~ 18 VDC (50 VA)
Operating Temp:	-31°F ~ 122°F (-35°C ~ 50°C)
Relative Humidity:	10-90 %
Weight:	13.26 lbs. (6 kg)
Shock:	≥4G
Environmental Rating:	IP66

DIMENSIONS (Unit: Inch, in the parentheses is mm)

